

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-R2

63.701.32

Double frame

- » For combining two SLT, LT or LS in flush-mounted installation

Material	Plastic
Colour	White
W x H	150 x 80 mm
Weight	0.10 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

PHZ 28

70.600.53

Profile semi-cylinder

- » For key vent button (SLT)
- » Including 3 keys

Weight	0.15 kg
--------	---------



LT Series Ventilation buttons

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-A 63.701.36

Ventilation button

- » For controlling a ventilation group
- » Suitable for surface-mounted installation in moisture-prone areas
- » Ventilation OPEN / STOP / CLOSED via double button with 2 unlocked normally open contacts

Input voltage	24 V DC
Type of protection	IP 44
Housing	Plastic
Colour	Light grey
W x H x D	70 x 70 x 45 mm
Weight	0.20 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

AP-LT 63.701.33

Surface-mounted housing, single

- » For holding one SLT, LT or LS for surface-mounted installation

Housing	Plastic
Colour	White
W x H x D	80 x 80 x 35 mm
Weight	0.10 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

AP2-LT 63.701.34

Surface-mounted housing, double

- » For holding two SLT, LT or LS for surface-mounted installation

Housing	Plastic
Colour	White
W x H x D	150 x 80 x 35 mm
Weight	0.20 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

SLT 42-U-SD

30.400.50

Key vent button



- » For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels
- » Function: Ventilation OPEN / CLOSED via key operated changeover contact
- » With integrated LED readout OPEN
- » For installing in deep 55 mm flush-mounted sockets (not included)
- » Profile semi-cylinder not included in scope of supply

Input voltage	24 V DC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H	80 x 80 mm
Weight	0.15 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

SLT 42-A

30.400.30

Key vent button



- » For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels
- » Function: Ventilation OPEN / CLOSED via key operated changeover contact
- » Profile semi-cylinder not included in scope of supply

Input voltage	24 V DC
Type of protection	IP 54
Housing	Aluminium
Colour	Light grey
W x H x D (max.)	70 x 90 x 65 mm
Weight	0.45 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

SLT 42-A-SD

30.400.40

Key vent button



- » For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels
- » Function: Ventilation OPEN / CLOSED via key operated changeover contact
- » With integrated LED readout OPEN
- » Profile semi-cylinder not included in scope of supply

Input voltage	24 V DC
Type of protection	IP 54
Housing	Aluminium
Colour	Light grey
W x H x D	70 x 90 x 65 mm
Weight	0.45 kg

LT Series Ventilation buttons

Type	Art. No.	Description	Technical data												
LS 84-U-V	63.701.45	Ventilation switch <ul style="list-style-type: none"> » For controlling a 230 V AC ventilation group » Ventilation OPEN / STOP / CLOSED via double button; buttons mechanically interlocked; STOP by repeated/renewed press of rocker switch back to starting position » For installing in 55 mm flush-mounted socket (not included) 	<table border="1"> <tr> <td>Input voltage</td> <td>230 V AC</td> </tr> <tr> <td>Type of protection</td> <td>IP 20</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>White</td> </tr> <tr> <td>W x H</td> <td>80 x 80 mm</td> </tr> <tr> <td>Weight</td> <td>0.30 kg</td> </tr> </table>	Input voltage	230 V AC	Type of protection	IP 20	Housing	Plastic	Colour	White	W x H	80 x 80 mm	Weight	0.30 kg
Input voltage	230 V AC														
Type of protection	IP 20														
Housing	Plastic														
Colour	White														
W x H	80 x 80 mm														
Weight	0.30 kg														



Type	Art. No.	Description	Technical data												
LT 84-U-W	63.701.31	Ventilation switch <ul style="list-style-type: none"> » Automatic switch for weather/temperature ON / OFF » For installing in 55 mm flush-mounted socket (not included) 	<table border="1"> <tr> <td>Input voltage</td> <td>24 V DC</td> </tr> <tr> <td>Type of protection</td> <td>IP 20</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>White</td> </tr> <tr> <td>W x H</td> <td>80 x 80 mm</td> </tr> <tr> <td>Weight</td> <td>0.30 kg</td> </tr> </table>	Input voltage	24 V DC	Type of protection	IP 20	Housing	Plastic	Colour	White	W x H	80 x 80 mm	Weight	0.30 kg
Input voltage	24 V DC														
Type of protection	IP 20														
Housing	Plastic														
Colour	White														
W x H	80 x 80 mm														
Weight	0.30 kg														



Type	Art. No.	Description	Technical data												
SLT 42-U	30.401.10	Key vent button <ul style="list-style-type: none"> » For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels » Function: Ventilation OPEN / CLOSED via key operated changeover contact » For installing in deep 55 mm flush-mounted sockets (not included) » Profile semi-cylinder not included in scope of supply 	<table border="1"> <tr> <td>Input voltage</td> <td>24 V DC</td> </tr> <tr> <td>Type of protection</td> <td>IP 20</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>White</td> </tr> <tr> <td>W x H</td> <td>80 x 80 mm</td> </tr> <tr> <td>Weight</td> <td>0.15 kg</td> </tr> </table>	Input voltage	24 V DC	Type of protection	IP 20	Housing	Plastic	Colour	White	W x H	80 x 80 mm	Weight	0.15 kg
Input voltage	24 V DC														
Type of protection	IP 20														
Housing	Plastic														
Colour	White														
W x H	80 x 80 mm														
Weight	0.15 kg														



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U 63.701.29

Ventilation button



- » For controlling a ventilation group
- » Ventilation OPEN / STOP / CLOSED via double button with 2 unlocked normally open contacts
- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	24 V DC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H	80 x 80 mm
Weight	0.15 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U-SD 63.701.35

Ventilation button



- » For controlling a ventilation group
- » Ventilation OPEN / STOP / CLOSED via double button with 2 unlocked normally open contacts
- » With integrated LED readout OPEN
- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	24 V DC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H	80 x 80 mm
Weight	0.15 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U-V 63.701.30

Ventilation button



- » For controlling a 230 V AC ventilation group
- » Ventilation OPEN / STOP / CLOSED via double button; buttons mechanically interlocked; STOP by releasing the button
- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	230 V AC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H	80 x 80 mm
Weight	0.30 kg

LT 84 / LS 84 / SLT 42



Performance features

- » For controlling ventilation drives
- » Self-explanatory symbols
- » Versions for flush-mounted and surface-mounted installation and for moisture-prone areas