



RC Series Radio remote control

Type	Art. No.	Description	Technical data																
RCM 024-11-U	30.554.60	Wireless receiving module																	
		<ul style="list-style-type: none"> » Wireless receiver with security encryption and code hopping principle » Up to 10 D+H wireless remote controls can be assigned » For installing in 55 mm flush-mounted socket (not included) » Ability to be controlled wirelessly via remote with secure 128 bit AES wireless encryption to protect against external control » For all 24 V DC D+H control panels » 2 group control outputs for connecting to the control panel ventilation button inputs 	<table border="1"> <tr> <td>Supply</td> <td>24 V DC / 0.03 A</td> </tr> <tr> <td>Type of protection</td> <td>IP 30</td> </tr> <tr> <td>Temperature range</td> <td>-5 °C ... +60 °C</td> </tr> <tr> <td>Radio frequency</td> <td>868.3 MHz / FSK</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>Grey</td> </tr> <tr> <td>W x H x D</td> <td>50 x 48 x 19 mm</td> </tr> <tr> <td>Weight</td> <td>0.07 kg</td> </tr> </table>	Supply	24 V DC / 0.03 A	Type of protection	IP 30	Temperature range	-5 °C ... +60 °C	Radio frequency	868.3 MHz / FSK	Housing	Plastic	Colour	Grey	W x H x D	50 x 48 x 19 mm	Weight	0.07 kg
Supply	24 V DC / 0.03 A																		
Type of protection	IP 30																		
Temperature range	-5 °C ... +60 °C																		
Radio frequency	868.3 MHz / FSK																		
Housing	Plastic																		
Colour	Grey																		
W x H x D	50 x 48 x 19 mm																		
Weight	0.07 kg																		

Type	Art. No.	Description	Technical data																
RCM 230-11-U	30.554.50	Wireless receiving module																	
		<ul style="list-style-type: none"> » Wireless receiver with security encryption and code hopping principle » Up to 10 D+H wireless remote controls can be assigned » For installing in 55 mm flush-mounted socket (not included) » Ability to be controlled wirelessly via remote with secure 128 bit AES wireless encryption to protect against external control » For direct control of 230 V AC drives » Switching capacity: max. 700 VA, 3 A, (resistive load) 	<table border="1"> <tr> <td>Supply</td> <td>230 V AC / 50 ... 60 Hz</td> </tr> <tr> <td>Type of protection</td> <td>IP 30</td> </tr> <tr> <td>Temperature range</td> <td>-5 °C ... +40 °C</td> </tr> <tr> <td>Radio frequency</td> <td>868.3 MHz / FSK</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>Grey</td> </tr> <tr> <td>W x H x D</td> <td>50 x 48 x 24 mm</td> </tr> <tr> <td>Weight</td> <td>0.08 kg</td> </tr> </table>	Supply	230 V AC / 50 ... 60 Hz	Type of protection	IP 30	Temperature range	-5 °C ... +40 °C	Radio frequency	868.3 MHz / FSK	Housing	Plastic	Colour	Grey	W x H x D	50 x 48 x 24 mm	Weight	0.08 kg
Supply	230 V AC / 50 ... 60 Hz																		
Type of protection	IP 30																		
Temperature range	-5 °C ... +40 °C																		
Radio frequency	868.3 MHz / FSK																		
Housing	Plastic																		
Colour	Grey																		
W x H x D	50 x 48 x 24 mm																		
Weight	0.08 kg																		

Type	Art. No.	Description	Technical data												
RCR 11-2	30.211.25	Wireless remote control <ul style="list-style-type: none"> » Ventilation OPEN / STOP / CLOSED » 868 MHz radio frequency, permitted throughout the EU » High level of security against external control – 32 bit address code and transmitting code change at each button press (hopping code) » With 2 functional levels 	<table border="1"> <tr> <td>Supply</td> <td>2 x Lithium CR 2032</td> </tr> <tr> <td>Transmitting power</td> <td>Approx. 1 mW (e.r.p)</td> </tr> <tr> <td>Transmitter range</td> <td>Max. 100 m free field</td> </tr> <tr> <td>Housing</td> <td>ABS, POM</td> </tr> <tr> <td>W x H x D</td> <td>45 x 110 x 15 mm</td> </tr> <tr> <td>Weight</td> <td>0.10 kg</td> </tr> </table>	Supply	2 x Lithium CR 2032	Transmitting power	Approx. 1 mW (e.r.p)	Transmitter range	Max. 100 m free field	Housing	ABS, POM	W x H x D	45 x 110 x 15 mm	Weight	0.10 kg
Supply	2 x Lithium CR 2032														
Transmitting power	Approx. 1 mW (e.r.p)														
Transmitter range	Max. 100 m free field														
Housing	ABS, POM														
W x H x D	45 x 110 x 15 mm														
Weight	0.10 kg														



Type	Art. No.	Description	Technical data												
RCR 11-4	30.211.50	Wireless remote control <ul style="list-style-type: none"> » Ventilation OPEN / STOP / CLOSED » 868 MHz radio frequency, permitted throughout the EU » High level of security against external control – 32 bit address code and transmitting code change at each button press (hopping code) » With 4 functional levels 	<table border="1"> <tr> <td>Supply</td> <td>2 x Lithium CR 2032</td> </tr> <tr> <td>Transmitting power</td> <td>Approx. 1 mW (e.r.p)</td> </tr> <tr> <td>Transmitter range</td> <td>Max. 100 m free field</td> </tr> <tr> <td>Housing</td> <td>ABS, POM</td> </tr> <tr> <td>W x H x D</td> <td>45 x 110 x 15 mm</td> </tr> <tr> <td>Weight</td> <td>0.10 kg</td> </tr> </table>	Supply	2 x Lithium CR 2032	Transmitting power	Approx. 1 mW (e.r.p)	Transmitter range	Max. 100 m free field	Housing	ABS, POM	W x H x D	45 x 110 x 15 mm	Weight	0.10 kg
Supply	2 x Lithium CR 2032														
Transmitting power	Approx. 1 mW (e.r.p)														
Transmitter range	Max. 100 m free field														
Housing	ABS, POM														
W x H x D	45 x 110 x 15 mm														
Weight	0.10 kg														



Type	Art. No.	Description	Technical data																
RCT 003-11-U	30.212.00	Wireless transmission module <ul style="list-style-type: none"> » For controlling D+H radio products with standard flush-mounted keys or isolated contacts » Ventilation OPEN / STOP / CLOSED » For installing in standard flush-mounted socket (not included) » Possible to connect to a room temperature control 	<table border="1"> <tr> <td>Supply</td> <td>1 x Lithium CR 2450</td> </tr> <tr> <td>Transmitting power</td> <td>Approx. 4 mW (e.r.p)</td> </tr> <tr> <td>Transmitter range</td> <td>Max. 100 m free field</td> </tr> <tr> <td>Radio frequency</td> <td>868.3 MHz / FSK</td> </tr> <tr> <td>Housing</td> <td>Plastic</td> </tr> <tr> <td>Colour</td> <td>Grey</td> </tr> <tr> <td>W x H x D</td> <td>45 x 39 x 12 mm</td> </tr> <tr> <td>Weight</td> <td>0.10 kg</td> </tr> </table>	Supply	1 x Lithium CR 2450	Transmitting power	Approx. 4 mW (e.r.p)	Transmitter range	Max. 100 m free field	Radio frequency	868.3 MHz / FSK	Housing	Plastic	Colour	Grey	W x H x D	45 x 39 x 12 mm	Weight	0.10 kg
Supply	1 x Lithium CR 2450																		
Transmitting power	Approx. 4 mW (e.r.p)																		
Transmitter range	Max. 100 m free field																		
Radio frequency	868.3 MHz / FSK																		
Housing	Plastic																		
Colour	Grey																		
W x H x D	45 x 39 x 12 mm																		
Weight	0.10 kg																		



RCR / RCT / RCM



Performance features

- » Transmitter, receiver and wireless remote control for D+H radio system
- » Resistant to interference thanks to transmitting code change
- » Easy installation and commissioning
- » Compatible with all D+H radio drives and control panels